



Dear Customer,

Thank you for purchasing our products. With your purchase, you support our small business

<https://www.3D4U-Freiburg.com>

and our hobby of developing, testing and marketing our own products for motorhomes for little money.

Thank you, Lars & Nils

Thank you for purchasing our RV sink siphon.

We hope you enjoy our article and above all - an odor-free sink.

Please read the entire installation description first before installation. Observe the following steps during installation.

Place a container under the drain and have a towel ready to collect residual water from the drain pipe.

1. Remove the existing drain by removing the central screw in the drain.
2. Gently clean the drain grate. This has a thin, very sensitive seal on the underside that quickly loses its shape.
3. Clean the drain opening of the sink from the top and bottom with the rough side of a dishwashing sponge and some washing-up liquid until everything is clean.
4. Open the hose clamp at the old drain and slide the clamp over the drain hose.
5. Remove the original drain from the drain hose with twisting movements and clean the hose opening here as well. Clean the black rubber seal of the drain thoroughly with rinse water. Ideally, lubricate them with a little Vaseline and place them in the opening of the new siphon.
6. As needed, wrap the siphon nozzle that is inserted into the sewer hose with a few turns of Teflon tape (sometimes already available from us). Insert the new siphon into the hose as far as possible and fix it with the hose clamp (not too tightly). **Please DO NOT shorten the waste water hose so that dismantling is possible at any time.**
7. Place a silicone strip about 2-3mm thick on the upper opening edge of the siphon.
8. From above, position the drain grid with the thin seal and screw centrally in the drain opening of the sink and fix it with your fingers so that it does not slip.
9. From above, screw the screw of the drain grate into the nut in the siphon, which will pull the siphon against the bottom of the sink from below. **Please tighten the screw only lightly to hand-tight.** If necessary, peel off silicone residues and allow to harden according to the manufacturer's instructions.

When commissioning, please check the siphon for tightness on the underside of the sink!

Other tips:

1. When installing, make sure that the waste water hose does not exceed the height of the siphon, but runs with a slight slope.
2. to prevent the liquid in the siphon from freezing, put some antifreeze in the drain for the winter or squeeze the water out of the siphon with a toilet plunger (then plug on it because odours now get through the siphon).
- Umwickeln Sie das Siphon am Anfang mit ein paar Blatt Küchenkrepp, um eventuelle Undichtigkeiten und einzelne Tropfen nach einigem Gebrauch zu erkennen.

Please understand that we cannot give any guarantee or warranty on the tightness of your installation.