

Dear Customer,

Thank you for purchasing our products. With your purchase, you support our small business

https://www3D4U-Freiburg.com

and our hobby of developing, testing and marketing our own products for motorhomes for little money.

Thank you, Lars & Nils

Please read the entire installation description first before installation. Observe the following steps during installation.

This siphon is intended for the silver, hemispherical sinks of the maple motorhomes and prevents odours from the grey water tank from entering the motorhome through the drain.

Please note that this siphon is *expressly* sold under *disclaimer* only and its use is at your own risk.

When winter approaches, please remember to remove the water from the siphon or alternatively fill 2cl AntiFreeze into the siphon.

When setting it up, check whether the siphon is leaking. Remove it if it is damaged and leaking.

For installation:

- 1. Place a large towel under the siphon area to catch any water residue. Under the sink, loosen the hose clamp on the drain hose and pull the hose from the drain nozzle. Please <u>do not</u> shorten the original drain hose so that dismantling remains possible at any time.
- 2. Now insert the angled end of the siphon into the drain hose and tighten the hose clamp slightly.
- 3. If desired, also use a hose clamp at the other end of the siphon (40mm).
- 4. Smear some dishwashing liquid/soap into the free end of the siphon. Now press the siphon over the drain nozzle and, if necessary, help with a small careful knock (from below on the siphon upwards towards the sink). Please <u>do not</u> try to move the siphon over the nozzle by means of rotary movements or force, as this can lead to tearing out of the fine thread during the drain nozzle. If the seat of the siphon is too tight, we recommend using some sandpaper to increase the inner diameter a little.

Please check the siphon for tightness on the underside of the washbasin when using it!

Other tips:

- When installing, make sure that the waste water hose <u>does not</u> exceed the height of the siphon, but runs with a slight slope.
- Wrap the siphon with a few sheets of kitchen paper at the beginning to detect any leaks and individual drops after some use.

Please understand that we cannot give any guarantee or warranty on the tightness of your installation.